

IP65-Rated, LED Par with Advanced RGBALC Color Mixing

Built to Impress

Outpost™ RGBALC is powered by 3x 20W 6-in-1 LEDs, offering bright, vibrant color mixing in a compact yet rugged design. Its silent, fanless housing ensures reliable operation in noise-sensitive environments, while the high-output LEDs provide powerful, even coverage. Indoors or outdoors, Outpost™ RGBALC fixtures can deliver outstanding results for a wide range of applications.

Fully Equipped

These fixtures offer 6/8/12-channel DMX modes + an intuitive 4-button OLED control menu with built-in programs, color presets, user-selectable 32-bit dimming curves, and virtual color wheel effects. They come with industry-standard 5-pin DMX input/output connections, a powerCON® TRUE1™ compatible input, and a single bracket for versatile rigging or freestanding use.

Luminous Intensity

Beam	2M	2.5M	3M	4M	5M
25°	3,927	2,495	1,716	950	592



Main Features

- Light source: 3x 20W RGBALC 6-in-1 LEDs
- 25-degree beam angle
- Flicker-free constant-current LED driver
- 6/8/12-channel DMX profiles with 32-bit dimming
- Multiple built-in programs and color presets
- Up to 3 customizable, 25 scene programs
- Virtual color wheel effects
- IP65-rated outdoor LED fixture
- Efficient convection cooling
- 4-button control menu with OLED display
- 5-pin DMX input & output connections
- PowerCON® TRUE1™ compatible power input
- Single bracket for rigging or freestanding
- Omega mounting points (bracket sold separately)



Optical

3x 20W RGBALC 6-in-1 LEDs, 100,000 hrs.

25° beam angle

Flicker-free LEDs



Weight & Dimensions

7.5" x 5.7" x 7.5" (190 x 143.8 x 191.5 mm)

4.8 lbs. (2.18 kg)

 $[\dagger \downarrow \dagger]$

Control

USITT DMX-512, RDM

5-pin DMX in/out

6/8/12-channel DMX modes

4-button menu with OLED display

DMX512, M/S, auto mode



Power + Current

100-240VAC, 50-60 Hz

Consumption: 50W, .43A, PF: .99

PowerCON® TRUE1compatible input



Warranty + Certifications

2-year limited warranty













